

Built-in 2 x 12 watt (RMS) amplifier  
Two inputs (1 x Minijack / 1 x 2-Phono)  
Adjustable-tilt wall brackets included



The SP-800P are Vision's most cost-effective audio solution. They are purpose-built for small meeting rooms and classrooms. Incredible value for money; they offer great sound quality and Vision's trademark ease of installation. Perfect for meeting spaces.

### 3-Way

A 4" woofer is complemented by a tweeter and squawker. Splitting the frequency spectrum across three drivers reduces distortion.

### Volume Control

The volume dial is positioned on the rear of the 'master' loudspeaker – the one containing the amplifier. Turning anti-clockwise turns power off.

### Horizontal C bracket

The adjustable brackets allow the installer to easily angle up 30° or down 30°. Or leave the brackets off and use as shelf speakers.

### Flexible Connectivity

The rear panel of the master loudspeaker offers minijack and 2-phono (RCA) inputs.

### ABS Chassis

Heavy-weight plastic material is used for the chassis, allowing a beautiful curved chassis and a rigid acoustic chamber for distortion-free sound.

### Bass Reflex

A bass reflex port allows greater excursion of the woofer, allowing the woofer to produce lower frequencies, and the phase-delayed movement of air from behind the woofer to the front reinforces the bass even more.

### Two Summed Line-level Inputs

The input panel offers minijack and 2-phono (RCA) line-level inputs which are combined at the input stage meaning there is no input selection switch. When both inputs are used it is especially important that all source and display devices in the system are powered from the same mains power source, otherwise earth hums will occur.

## SPECIFICATIONS

**PRODUCT DIMENSIONS**

202 x 149 x 144 mm / 7.95" x 5.87" x 5.67"(tall x wide x deep for each speaker)

**PACKAGED DIMENSIONS**

370 x 170 x 215 mm / 14.6" x 6.7" x 8.7"

**PRODUCT WEIGHT**

3.4 kg / 7.5 lb (per pair)

**PACKAGED WEIGHT**

3.5 kg /7.7 lb (per pair)

**CONSTRUCTION MATERIAL**

ABS Plastic

**COLOUR**

White

**AMPLIFIER OUTPUT**

2 x 12w watts (RMS)

**WOOFER**

4"

**TWEETER**

1"

**SQUAWKER**

2"

**INPUT 1**

Minijack (3.5mm)

**INPUT 2**

2-Phono (RCA)

**SPEAKER OUTPUT**

Removable Phoenix type

**SPEAKER INPUT (ON SLAVE)**

Removable Phoenix type

**OUTPUT IMPEDANCE**

4 ohms

**SENSITIVITY**

85dB (1w/1m)

**FREQUENCY RESPONSE**

100Hz-16kHz

**ACCESSORIES INCLUDED**

2 x Wall brackets 1 x Speaker Cable 5m (16.4 ft) Note: no input cables are included

**POWER SUPPLY**

100-240v 50/60Hz AC External Power Supply – 18 volt / 1 amp

**TRANSFORMER INTEGRATED INTO PLUG****INCLUDES INTERCHANGEABLE PLUGS**

UK/EU/US/AU

**DC TAIL LENGTH**

1.5m (5ft)

**TRANSFORMER DIMENSIONS**

75 x 38 x 50mm / 3" x 1.5" x 2" (tall x wide x deep) including prongs

**WARRANTY**

Lifetime return-to-base

**COMPLIANCE**

RoHS, WEEE, CE/EMC, FCC, RCM-POC, RCM-SDOC, REACH

**SPARE POWER SUPPLY UNIT (PSU)**

TC2 P18V1A [EU SAP: 3675051/ US SAP: 13445526]

