

### Basic HDMI Faceplate Package

Mounting hardware: single-gang backbox and surround

Modules: HDMI and USB 3.0

Input cables: 3 m HDMI and USB

Output cables: 10 m HDMI and USB



Techconnect is Europe's most popular modular audio-visual faceplate engineered especially for AV installers. It is made up of a "surround" that fits to a backbox, then the modules fix in place to complete the installation. Techconnect is based around standard UK backbox sizes.

This package features everything professional AV installers need for most basic interactive projector or display installations. It is a simple package that contains a basic selection of modules as a starting point, plus input and output cables.

We know from two decades of supporting our customers that most connectivity issues are caused by poor quality input cables. For normal consumers applications a 2 or 3 metre cable doesn't need to be premium quality, but when you introduce joins and longer cables every link in the signal chain needs to be optimised. So by using Vision cable for input and output you know that the signal bandwidth will be maintained.

#### Modules Included

1 x HDMI

1 x USB 3.0

"A" type socket on the rear (the rectangle shape)

"B" type socket on the front (the square shape)

Note: these modules do not include active booster circuits. If you experience issues try the booster modules (TC3 USB+ and TC3 HDMI+)

#### Easy assembly

Techconnect is easy to install and has more space behind the modules to stash cables.

#### Space for labelling

The surround is white with a chiselled profile, and it has 11 mm of space above and below the modules for information or company branding stickers.

#### Stronger

Techconnect has extra ribbing to reduce module flex and the plastic won't go brittle. We have designed them to last a lifetime.

#### Screw-In Modules

The modules have a tab that hooks into the surround at the bottom, then a couple of turns of the pre-installed screws locks the modules into place.

### Future-proof

A family of modules work in the same surround, so if you ever need to change anything it is easy.

### No Soldering

Faceplates that require soldering take time build onsite, and – even for experts – create a possible point of failure in the system. Techconnect de-risks an installation.

### Cables Included

Input Cables (from source to faceplate)

3 m HDMI

3 m USB

Output Cables: (from faceplate to display)

10 m HDMI

10 m USB with active booster

### 4K Ready

This system supports 4K @ 60 Hz. Note: some display and source combinations won't allow 60 Hz because they are more sensitive to signal degradation.

## SPECIFICATIONS

### BACKBOX DIMENSIONS

86 x 86 x 45 mm / 3.39" x 3.39" x 1.77"

### SURROUND DIMENSIONS

86 x 86 x 8 mm / 3.39" x 3.39" x 0.31"

### CARTON DIMENSIONS

160 x 95 x 60 mm (6.3"x 3.74" x 2.36")

### PACKAGED WEIGHT

0.3 kg /0.66 lb

### COLOUR

Modules and Mounting Hardware: White Cables: White

### HDMI MODULE SPEC

HDMI Standard: v2.0 Conductor Thickness: AWG 26 Resolution: 4K @ 60 Hz (refresh rate dependent on source and display combination) Tail length: 200 mm (7.9") Material: ABS Dimensions: 64 x 21 mm / 2.5" x 0.8" (height x width)

### USB MODULE SPEC

USB Standard: USB 3.0 Material: ABS Tail length: 200 mm (7.9")

Dimensions: 64 x 21 mm / 2.5" x 0.8" (height x width)

### USB CABLE SPEC

USB Standard: 2.0 Active Booster: inline active booster half way along cable Bandwidth: 480 Mbit/s Conductor Thickness: AWG 28+24 Outer Sheath Diameter: 4.5 mm (0.2") Outer Sheath Material: PVC Insulation Material: HDPE Connectors: gold plated Shielding: More than 65% coverage braided EMF Protection: Ferrite core at both ends

### HDMI CABLE SPEC

HDMI Standard: v2.0 High Speed Category 2 with Ethernet Bandwidth: 340 MHz Data Transfer rate: 18 Gbit/s Conductor Thickness: AWG 26 Resolution: 4K @ 60 Hz Outer Sheath Diameter: 8.0 mm Connectors: gold plated Shielding: double shielded Audio Return Channel: yes

### COMPLIANCES

RoHS, WEEE, CE