



# Braided DisplayPort to HDMI Cable 1 m (3.2ft)

TC 1MDPHDMI/HQ EU SAP: 4911562 US SAP: 13557596

[vav.link/tc\\_1mdphdmi-hq](http://vav.link/tc_1mdphdmi-hq)

Allows PCs with 'Dual-Mode' DisplayPort (DP++) outputs to connect to displays with HDMI inputs.



## Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

## Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.



VISION

## IMAGE

Product Images

**ZIP 553.18 KB**

[files.visionaudiovisual.com/products/TC\\_1MDPHDMI/images/TC\\_1MDPHDMI.zip](files.visionaudiovisual.com/products/TC_1MDPHDMI/images/TC_1MDPHDMI.zip)

Image 1

**PNG 770.88 KB**

[files.visionaudiovisual.com/products/TC\\_1MDPHDMI-HQ/images/TC\\_1MDPHDMI-HQ\\_1.png](files.visionaudiovisual.com/products/TC_1MDPHDMI-HQ/images/TC_1MDPHDMI-HQ_1.png)

Image 2

**PNG 437.74 KB**

[files.visionaudiovisual.com/products/TC\\_1MDPHDMI-HQ/images/TC\\_1MDPHDMI-HQ\\_2.png](files.visionaudiovisual.com/products/TC_1MDPHDMI-HQ/images/TC_1MDPHDMI-HQ_2.png)

Image 3

**PNG 1.02 MB**

[files.visionaudiovisual.com/products/TC\\_1MDPHDMI-HQ/images/TC\\_1MDPHDMI-HQ\\_3.png](files.visionaudiovisual.com/products/TC_1MDPHDMI-HQ/images/TC_1MDPHDMI-HQ_3.png)

## SPECIFICATIONS

### MAXIMUM RESOLUTION

4k @ 60 Hz (note: at time of writing no chipset supports 60Hz)

### CONTACT RESISTANCE

2 ohm max

### SHEATH OUTER DIAMETER

6.0 mm (0.24")

### CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

### PACKAGED WEIGHT

0.16 kg (0.35 lb)

### PRODUCT WEIGHT

0.11 kg (0.24 lb)

### PACKAGED DIMENSIONS

160 mm x 160 mm x 43 mm (6.3" x 6.3" x 1.7")

### COLOUR

Braided

### DP VERSION

1.3

### 4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP

PS176 CHIPSET