



hvidt CAT6-kabel 20 m

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

vav.link/da/tc_20mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip

Product Images

PNG 834.77 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT6.png

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png

SPECIFICATIONS

ISOLERING

HDPE, diameter: 0,97 mm (0,04")

HYLSTER

PVC, tykkelse: 0,6 mm (0,02"), udvendig diameter: 6,2 mm (0,24")

LEDERTYKKELSE

24 AWG (7/0,2)

BÅNDBREDDE

250 MHz

IMPEDANS (Ω)

100±15

FORSINKET FORSKYDNING VED 20°C (NS/100 M)

≤45

PAKKET VÆGT

0,87 kg (1,9 lb)

PAKKET DIMENSION

260 mm x 320 mm (10,2" x 12,6")

U/UTP (USKÆRMET)

LEDERE AF KOBBERTRÅD

GULDBELAGT RJ45 STIK MED SKO

