

CAT6-Kabel, 20 m, weiß

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

vav.link/de/tc_20mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip

Product Images




PNG 834.77 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT5.png

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png



SPECIFICATIONS

ISOLIERUNG

HDPE, Durchmesser: 0,97 mm (0,03")

UMMANTELUNG

PVC, Stärke: 0,6 mm (0,02"); Außendurchmesser: 6,2 mm (0,24")

LEITERSTÄRKE

24 AWG (7/0,2)

BANDBREITE

250 MHz

IMPEDANZ (Ω)

100±15

LAUFZEITDIFFERENZ BEI 20 °C (NS/100 M)

≤ 45

VERPACKTES GEWICHT

0,87 kg (1,9 lb)

ABGEPAKTE DIMENSION

260 mm x 320 mm (10,2" x 12,6")

U/UTP (NICHT ABGESCHIRMT)

MEHRDRÄHTIGER KUPFERLEITER

VERGOLDETE RJ45-STECKER MIT KNICKSCHUTZ