



White CAT6 Cable 20m (65.6ft)

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

vav.link/tc_20mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip

Product Images




PNG 834.77 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT5.png

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png



SPECIFICATIONS

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.87 kg (1.9 lb)

PACKAGED DIMENSIONS

260 mm x 320 mm (10.2" x 12.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS