



Cavo CAT6 bianco da 20 m (65,6 piedi)

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

vav.link/it/tc_20mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip

Product Images




PNG 834.77 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT5.png

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png



SPECIFICATIONS

ISOLAMENTO

HDPE, diametro: 0,97 mm (0,04")

GUAINA

PVC, spessore: 0,6 mm (0,02"), diametro esterno: 6,2 mm (0,24")

SPESSORE DEL CONDUTTORE

24 AWG (7/0,2)

LARGHEZZA DI BANDA

250 MHz

IMPEDENZA (Ω)

100±15

RITARDO DELLA DISTORSIONE @ 20°C(NS/100 M)

≤45

PESO CONFEZIONATO

0,87 kg (1,9 libbre)

DIMENSIONE CONFEZIONATA

260 mm x 320 mm (10,2" x 12,6")

U/UTP (NON SCHERMATO)

CONDUTTORI A TREFOLI IN RAME SCOPERTO

CONNETTORI RJ45 PLACCATI IN ORO CON COPRICONNETTORI