



## witte CAT6-kabel 20 m (65,6 ft)

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

[vav.link/nl/tc\\_20mcat6](http://vav.link/nl/tc_20mcat6)

**VISION**



## IMAGE

Product Images

**ZIP 813.29 KB**

[files.visionaudiovisual.com/products/TC\\_20MCAT6/images/TC\\_20MCAT6.zip](files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip)

Product Images

**PNG 834.77 KB**

[files.visionaudiovisual.com/products/TC\\_20MCAT6/images/TC-XXMCAT5.png](files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT5.png)

Product Images

**PNG 3.01 KB**

[files.visionaudiovisual.com/products/TC\\_20MCAT6/images/TC-CAT6.png](files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png)

## SPECIFICATIONS

### ISOLATIE

HDPE; diameter: 0,97mm (0,04")

### MANTEL

PVC, dikte: 0,6mm (0,02"); Buitendiameter: 6,2mm (0,24")

### KABELDIKTE

24AWG (7/0,2)

### BANDBREEDTE

250MHz

### IMPEDANTIE ( $\Omega$ )

100±15

### VERTRAGING BIJ 20°C(NS/100M)

≤45

### VERPAKT GEWICHT

0,04 kg (0,09 lb)

### VERPAKTE DIMENSIE

260 mm x 320 mm (10,2" x 12,6")

### U/UTP (ONBESCHERMD)

GESLAGEN BLANKE KOPEREN KABELS

VERGULDE RJ45 CONNECTORS MET HULS

