



Cabo CAT6 de qualidade branco, 20 m

TC 20MCAT6 EU SAP: 3265150 US SAP: 12939585

vav.link/pt-pt/tc_20mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC_20MCAT6.zip

Product Images




PNG 834.77 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-XXMCAT5.png

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_20MCAT6/images/TC-CAT6.png



SPECIFICATIONS

ISOLAMENTO

HDPE; diâmetro: 0,97mm (0,04")

REVESTIMENTO

PVC; espessura: 0,6 mm (0,02"); diâmetro exterior: 6,2mm (0,24")

ESPESSURA DO CONDUTOR

24 AWG (7/0,2)

LARGURA DE BANDA

250 MHz

IMPEDÂNCIA (Ω)

100±15

OBLIQUIDADE DO ATRASO @ 20°C(NS/100M)

≤45

PESO EMPACOTADO

0,87 kg (1,9 lb)

DIMENSÃO EMPACOTADA

220 mm x 270 mm (8,6" x 10,6")

U/UTP (NÃO BLINDADO)

CONDUTORES DE COBRE NU ENTRANÇADOS

CONECTORES RJ45 EMBUTIDOS FOLHEADOS A OURO