Braided USB-C to USB 3.0A Cable

vav.link/tc-xmusbca-hq

Lifetime warranty

On one end: USB A - plugs into the old connector on your laptop and carries USB 3.0 signal.

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

1m **(3.2ft)** END OF LIFE AUGUST 2021
TC 1MUSBCA/HQ EU SAP: 4911579 US SAP: 13557656

2m **(6.5ft)** END OF LIFE AUGUST 2021
TC 2MUSBCA/HQ EU SAP: 4911580 US SAP: 13557657

SPECIFICATIONS

TC 1MUSBCA/HQ Braided USB-C to USB 3.0A Cable 1m (3.2ft)

SHEATH: PVC, OUTER DIAMETER
4.5 mm (0.18")

CONDUCTOR THICKNESS
22+30 AWG

BANDWIDTH
480Mbit/s

CHARGING CURRENT
3 A

COMPLIANCE
RoHS, CE, FCC

PACKAGED WEIGHT
0.08 kg (0.17 lb)

PRODUCT WEIGHT
0.03 kg (0.06 lb)

PACKAGED DIMENSIONS
150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR
Braided

LENGTH
1m (3.2ft)

USB 3.0 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 2MUSBCA/HQ Braided USB-C to USB 3.0A Cable 2m (6.5ft)

SHEATH: PVC, OUTER DIAMETER
4.5 mm (0.18")

CONDUCTOR THICKNESS
22+30 AWG

BANDWIDTH
480Mbit/s

CHARGING CURRENT
3 A

COMPLIANCE
RoHS, CE, FCC

PACKAGED WEIGHT
0.06 kg (0.13 lb)

PRODUCT WEIGHT
0.11 kg (0.24 lb)

PACKAGED DIMENSIONS
150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR
Braided

LENGTH
2m (6.5ft)

USB 3.0 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB