



## White DisplayPort to HDMI Cable 4m (13.1ft)

TC 4MDPHDMI EU SAP: 3265168

[vav.link/tc\\_4mdphdmi](https://vav.link/tc_4mdphdmi)

Allows PCs with 'Dual-Mode' DisplayPort (DP++) outputs to connect to displays with HDMI inputs.

VISION



## IMAGE

Product Images

**ZIP 553.18 KB**

[files.visionaudiovisual.com/products/TC\\_4MDPHDMI/images/TC\\_4MDPHDMI.zip](files.visionaudiovisual.com/products/TC_4MDPHDMI/images/TC_4MDPHDMI.zip)

Product Images


**PNG 551.14 KB**

[files.visionaudiovisual.com/products/TC\\_4MDPHDMI/images/TC-XXMDPHDMI.png](files.visionaudiovisual.com/products/TC_4MDPHDMI/images/TC-XXMDPHDMI.png)

Product Images

**PNG 31.36 KB**

[files.visionaudiovisual.com/products/TC\\_4MDPHDMI/images/TC-1M4M-DPHDMI.png](files.visionaudiovisual.com/products/TC_4MDPHDMI/images/TC-1M4M-DPHDMI.png)



## SPECIFICATIONS

### MAXIMUM RESOLUTION

4k @ 30 Hz (note: at time of writing no chipset supports 60Hz)

### CONTACT RESISTANCE

2 ohm max

### SHEATH OUTER DIAMETER

5.5 mm (0.22")

### CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

### PACKAGED WEIGHT

0.19 kg (0.42 lb)

### PACKAGED DIMENSION

220 mm x 270 mm (8.7" x 10.6")

### 4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP